



F3 : Diglycidyl ether of Bisphénol A, Silica cristalline, Trimethylolpropane triglycidyl ether, Ethylene glycol and Titanium Dioxide based product

Section 1. Identification		
Product identifier	Anchoring Epoxy FastSet (Part A) Anchoring Epoxy High Strength (Part A)	
Other means of identification	862055, 866056	
Recommended use and restrictions on use	Epoxies for anchoring objects to concrete	
Initial supplier identifier	Les Produits Daubois Inc. 6155 boul. des Grandes-Prairies, St-Léonard (Québec) H1P 1A5 Tél. 514-328-1253	
Emergency telephone number/restriction on use	Canada – CANUTEC 613-996-6666	
Section 2. Hazard identification		
Classification of hazardous product (name of the category or subcategory of the hazard class)		
Skin corrosion (Category 1) Eye damage (Category 1) Sensitization – Skin (Category 1) Carcinogenicity (Category 1) Reproductive toxicity (Category 2) Specific target organ toxicity – repeated exposure (Category 1), Organs Hazardous to the aquatic environment – Chronic (Category 2)		
Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)		
<p>DANGER</p> <p>H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H350 May cause cancer. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs (lungs/kidneys) through prolonged or repeated exposure (inhalation/ingestion). H411 Toxic to aquatic life with long lasting effects.</p> <p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dusts or mists. P264 Wash hands/nails/face thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308+P313 IF exposed or concerned: Get medical attention. P314 Get medical attention if you feel unwell. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P363 Wash contaminated clothing before reuse. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 Immediately call a doctor. P273 Avoid release to the environment. P391 Collect spillage. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.</p>		
Other hazards known	None	
Section 3. Composition/information on ingredients		
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*
Diglycidyl Ether of Bisphenol A	25085-99-8	30-60
Silica, Crystalline (Quartz)/Sand	14808-60-7	40-70
Trimethylolpropane triglycidyl ether	30499-70-8	< 15
Ethylene glycol	107-21-1	< 5
Titanium dioxide	13463-67-7	< 5
* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) by weight (except for gases/propellants by volume) considered trade secret(s).		

Section 4. First-aid measures	
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor.
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. (15-20 minutes).



Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. (15-20 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.		
Most important symptoms and effects (acute or delayed)	Eye and skin damage.		
Indication of immediate medical attention/special treatment	In all cases, call a doctor. Do not forget this document.		
Section 5. Fire-fighting measures			
Specific hazards of the hazardous product (hazardous combustion products)			
Carbon oxides and other irritant/toxic gases and fumes.			
Suitable and unsuitable extinguishing media			
In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish surrounding products.			
Special protective equipment and precautions for fire-fighters			
During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.			
Section 6. Accidental release measures			
Personal precautions, protective equipment and emergency procedures			
Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).			
Methods and materials for containment and cleaning up			
Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.			
Section 7. Handling and storage			
Precautions for safe handling			
Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.			
Conditions for safe storage, including any incompatibilities			
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.			
Section 8. Exposure controls/Personal protection			
Control parameters (biological limit values or exposure limit values and source of those values)			
Exposure limits: CAS 13463-67-7 ACGIH – TLV-TWA 10 mg/m ³ & PEL-TWA 10 mg/m ³ ; CAS 14808-60-7 ACGIH – TLV-TWA 0.025 mg/m ³ & PEL-TWA 0.1 mg/m ³ ; Dust PEL-TWA 5 mg/m ³ (respirable fraction) & 15 mg/m ³ (total dust)			
Appropriate engineering controls			
Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.			
Individual protection measures/personal protective equipment			
Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.			
Section 9. Physical and chemical properties			
Appearance, physical state/colour	White paste	Vapour pressure	Not available
Odour	Characteristic	Vapour density	Not available
Odour threshold	Not available	Relative density	Not available
pH	Not available	Solubility	Not available
Melting/freezing point	Not available	Partition coefficient - n-octanol/water	Not available
Initial boiling point/range	Not available	Auto-ignition temperature	Not available
Flash point	> 93°C	Decomposition temperature	Not available
Evaporation rate	Not available	Viscosity	Not available



Flammability (solids and gases)	Not available	VOC	Not available
Upper and lower flammability/explosive limits	Not available	Other	None known
Section 10. Stability and reactivity			
Reactivity			
Does not react under the recommended storage and handling conditions prescribed.			
Chemical stability			
Stable under the recommended storage and handling conditions prescribed.			
Possibility of hazardous reactions			
None known.			
Conditions to avoid (static discharge, shock or vibration)			
None known.			
Incompatible materials			
Oxidizing materials; etc.			
Hazardous decomposition products			
None known			
Section 11. Toxicological information			
Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)			
Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (lungs/kidneys) through prolonged or repeated exposure (inhalation/ingestion).			
Symptoms related to the physical, chemical and toxicological characteristics			
Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing. Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.			
Delayed and immediate effects (chronic effects from short-term and long-term exposure)			
Skin Sensitization – Possible; Respiratory Sensitization – No data available; Germ Cell Mutagenicity – No data available; Carcinogenicity – Ingredient listed by IARC, ACGIH, NTP or OSHA Reproductive Toxicity – Possible; Specific Target Organ Toxicity — Single Exposure – No data available; Specific Target Organ Toxicity — Repeated Exposure – Possible; Aspiration Hazard – No data available; Health Hazards Not Otherwise Classified – No data available.			
Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)			
CAS 107-21-1 LD ₅₀ Oral - Rat – 4700 mg/kg; ATE not available in this document.			
Section 12. Ecological information			
Ecotoxicity (aquatic and terrestrial information)			
No data available for the product.			
Persistence and degradability	No data available		
Bioaccumulative potential	No data available		
Mobility in soil	No data available		
Other adverse effects	Toxic to aquatic life with long lasting effects.		
Section 13. Disposal considerations			
Information on safe handling for disposal/methods of disposal/contaminated packaging			
Dispose of contents/container into safe container in accordance with local, regional or national regulations.			

Section 14. Transport information	
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG/49 CFR Regulations	
UN1759; CORROSIVE SOLID, N.O.S. (Trimethylolpropane triglycidyl ether); CLASS 8; PG III	
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)	
UN1759; CORROSIVE SOLID, N.O.S. (Trimethylolpropane triglycidyl ether); CLASS 8; PG III	
UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)	
UN1759; CORROSIVE SOLID, N.O.S. (Trimethylolpropane triglycidyl ether); CLASS 8; PG III	
Special precautions (transport/conveyance)	May also be shipped as a LIMITED QUANTITY in accordance with TDG.
Environmental hazards (IMDG or other)	Marine pollutant
Bulk transport (usually more than 450 L in capacity)	Possible
Section 15. Regulatory information	
Safety/health Canadian regulations specifics	Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).



Environmental Canadian regulations specifics	Refer to Section 3 for ingredient(s) of the DSL
Safety/health/environmental outside regulations specifics	
<p>United States OSHA information: This product is regulated according to OSHA (29 CFR). United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3. National Fire Protection Association (NFPA): HEALTH: 3 FLAMMABILITY: 1 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3. HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe California Proposition 65: WARNING This product contains Silica, Crystalline (Quartz) & Titanium dioxide known to the State of California to cause cancer or other reproductive harm.</p>	
Section 16. Other information	
Date of the latest revision of the safety data sheet	February 18, 2022 version 2 (NSS ENTREPRISE INC.)
Corrections	New template
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.
Abbreviations	
ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System
<p>To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>	



F3 : Silica cristalline, Nonylphenol, 2-Piperazin-1-Ylethylamine and Dimethylaminomethyl based product

Section 1. Identification		
Product identifier	Anchoring Epoxy FastSet (Part B) Anchoring Epoxy High Strength (Part B)	
Other means of identification	862055, 866056	
Recommended use and restrictions on use	Epoxies for anchoring objects to concrete	
Initial supplier identifier	Les Produits Daubois Inc. 6155 boul. des Grandes-Prairies, St-Léonard (Québec) HIP 1A5 Tel. 514-328-1253	
Emergency telephone number/restriction on use	Canada – CANUTEC 613-996-6666	
Section 2. Hazard identification		
Classification of hazardous product (name of the category or subcategory of the hazard class)		
Skin corrosion (Category 1) - Eye damage (Category 1) - Sensitization – Skin (Category 1) - Carcinogenicity (Category 1) Reproductive toxicity (Category 2) - Specific target organ toxicity – repeated exposure (Category 1), Organs Hazardous to the aquatic environment – Chronic (Category 1)		
Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)		
<p>DANGER</p> <p>H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H350 May cause cancer. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation). H410 Very toxic to aquatic life with long lasting effects.</p> <p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dusts or mists. P264 Wash hands/nails/face thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308+P313 IF exposed or concerned: Get medical attention. P314 Get medical attention if you feel unwell. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P363 Wash contaminated clothing before reuse. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 Immediately call a doctor. P273 Avoid release to the environment. P391 Collect spillage. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.</p>		
Other hazards known	None	
Section 3. Composition/information on ingredients		
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*
Silica, Crystalline (Quartz)/Sand	14808-60-7	40-70
4-Nonylphenol, Branched	84852-15-3	10-30
2-Piperazin-1-Ylethylamine	140-31-8	10-30
2,4,6-tris(Dimethylaminomethyl) phenol	90-72-2	3-7
Benzyl alcohol	100-51-8	1-5
Diaminopolypropylene glycol	9046-10-0	1-5
Bis[(Dimethylamino)methyl]phenol	71074-89-0	1-5
2-(2-Aminoethylamino) ethanol	111-41-1	< 1
* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) by weight (except for gases/propellants by volume) considered trade secret(s).		

Section 4. First-aid measures	
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor.
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. (15-20 minutes).
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. (15-20 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.



Most important symptoms and effects (acute or delayed)	Eye and skin damage.		
Indication of immediate medical attention/special treatment	In all cases, call a doctor. Do not forget this document.		
Section 5. Fire-fighting measures			
Specific hazards of the hazardous product (hazardous combustion products)			
Carbon oxides and other irritant/toxic gases and fumes.			
Suitable and unsuitable extinguishing media			
In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish surrounding products.			
Special protective equipment and precautions for fire-fighters			
During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.			
Section 6. Accidental release measures			
Personal precautions, protective equipment and emergency procedures			
Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).			
Methods and materials for containment and cleaning up			
Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.			
Section 7. Handling and storage			
Precautions for safe handling			
Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.			
Conditions for safe storage, including any incompatibilities			
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.			
Section 8. Exposure controls/Personal protection			
Control parameters (biological limit values or exposure limit values and source of those values)			
Exposure limits: CAS 14808-60-7 ACGIH – TLV-TWA 0.025 mg/m ³ & PEL-TWA 0.1 mg/m ³ ; CAS 111-41-1 – ACGIH – TLV-TWA 1 ppm; Dust PEL-TWA 5 mg/m ³ (respirable fraction) & 15 mg/m ³ (total dust)			
Appropriate engineering controls			
Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.			
Individual protection measures/personal protective equipment			
Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.			
Section 9. Physical and chemical properties			
Appearance, physical state/colour	Black paste/liquid	Vapour pressure	Not available
Odour	Characteristic	Vapour density	Not available
Odour threshold	Not available	Relative density	Not available
pH	Not available	Solubility	Not available
Melting/freezing point	Not available	Partition coefficient - n-octanol/water	Not available
Initial boiling point/range	Not available	Auto-ignition temperature	Not available
Flash point	> 93°C	Decomposition temperature	Not available
Evaporation rate	Not available	Viscosity	Not available
Flammability (solids and gases)	Not available	VOC	Not available



Upper and lower flammability/explosive limits	Not available	Other	None known
---	---------------	-------	------------

Section 10. Stability and reactivity

Reactivity

Does not react under the recommended storage and handling conditions prescribed.

Chemical stability

Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

None known.

Conditions to avoid (static discharge, shock or vibration)

None known.

Incompatible materials

Oxidizing materials; etc.

Hazardous decomposition products

None known

Section 11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation).

Symptoms related to the physical, chemical and toxicological characteristics

Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing. Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – Possible; Respiratory Sensitization – No data available; Germ Cell Mutagenicity – No data available; Carcinogenicity – Ingredient listed by IARC, ACGIH, NTP or OSHA Reproductive Toxicity – Possible; Specific Target Organ Toxicity — Single Exposure – No data available; Specific Target Organ Toxicity — Repeated Exposure – Possible; Aspiration Hazard – No data available; Health Hazards Not Otherwise Classified – No data available.

Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)

CAS 84852-15-3 LD₅₀ Oral - Rat – 1246 mg/kg & LD₅₀ Dermal - Rabbit – 2040 mg/kg; CAS 100-51-6 LD₅₀, Oral - Rat 1360 mg/kg; CAS 90-72-2 LD₅₀ Oral - Rat – 2196 mg/kg; ATE not available in this document.

Section 12. Ecological information

Ecotoxicity (aquatic and terrestrial information)

No data available for the product.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Very toxic to aquatic life with long lasting effects.

Section 13. Disposal considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Section 14. Transport information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG/49 CFR Regulations

UN2735; POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2-Piperazin-1-Ylethylamine; 4-Nonylphenol, Branched); CLASS 8; PG III

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)

UN2735; POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2-Piperazin-1-Ylethylamine; 4-Nonylphenol, Branched); CLASS 8; PG III

UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)

UN2735; POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2-Piperazin-1-Ylethylamine; 4-Nonylphenol, Branched); CLASS 8; PG III

Special precautions (transport/conveyance)

May also be shipped as a LIMITED QUANTITY in accordance with TDG.

Environmental hazards (IMDG or other)

Marine pollutant

Bulk transport (usually more than 450 L in capacity)

Possible



Section 15. Regulatory information	
Safety/health Canadian regulations specifics	Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).
Environmental Canadian regulations specifics	Refer to Section 3 for ingredient(s) of the DSL
Safety/health/environmental outside regulations specifics	
United States OSHA information: This product is regulated according to OSHA (29 CFR). United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3. National Fire Protection Association (NFPA): HEALTH: 3 FLAMMABILITY: 1 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3. HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe California Proposition 65: WARNING This product contains Silica, Crystalline (Quartz) known to the State of California to cause cancer or other reproductive harm.	
Section 16. Other information	
Date of the latest revision of the safety data sheet	February 18, 2022 version 2 (NSS ENTREPRISE INC.)
Corrections	New template
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.
Abbreviations	
ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.	