


Asphalt -20 °C



1-Product description

1.1 USE

- bomix® asphalt -20 °C is a bituminous surfacing compound specially developed to be applied during winter time.
- Mostly used by municipalities, it is ideal for reparation of roads, driveways and parking areas in winter months.
- bomix® asphalt -20 °C remains workable down to a temperature of -20 °C (4 °F).

2- Installation

2.1 SURFACE PREPARATION

- Clean area to be repaired with a heavy broom or a brush. Remove all loose matter, mud, water, etc..

2.2 APPLICATION

- Fill the area with bomix® asphalt -20 °C to approximately 12 mm (1/2 in) above the level of surrounding pavement.
- Level with a lawn roller, a hand-stamper or the flat face of a shovel. NOTE: Resistance will depend on the degree of compaction. This step is very important.
- In mild weather, it is suggested to add a small amount of sand or dust on the surface to prevent the asphalt from sticking onto the tools or tires.
- bomix® asphalt -20 °C does not require any curing time, the surface may be used as soon as the work is completed.

2.3 YIELD

- A 30 kg (66 lb) bag will cover approximately 0,014 m³ (0,5 ft³).

2.4 CLEANING

- Mineral spirit is an excellent solvent to clean tools.

3. Packaging

- This product is available in 30 kg (66 lb) plastic bag.

4. Storage

- Store in a cool, dry place. Keep away from heat sources.
- Shelf life is two years in unopened bags.

5. First aid

This product contains naphtha and may cause eye and skin irritation. Wear rubber gloves and safety glasses. If swallowed, call a Poison Control centre or doctor immediately. Give approximately 250 ml of water to the victim if she is conscious. Do not induce vomiting. In case of contact with eyes, rinse well with water for 15 minutes. In case of skin contact, rinse well with water. Keep out of reach of children. Consult the safety data sheet for more information.

6. Technical services

Contact Daubois for more information about application methods or conditions or to obtain the latest version of our technical documents.

Phone: 1-800-561-2664
(514) 328-1253

Fax: (514) 328-7694

Daubois inc
6155, boul. des Grandes Prairies
Saint-Léonard, Qc H1P 1A5
Canada
<http://www.daubois.com>

7. Warranty

Daubois guarantees that this product will perform as specified in this technical data sheet and suits the application for which it was intended. Nonetheless, Daubois does not offer any explicit or implicit warranty. Under this warranty, Daubois' responsibility is limited to either replace or refund the cost of the product proved defective.