

Asphalt



1-Product description

1.1 USE

- bomix® asphalt is a bituminous surfacing compound for the reparation of driveways, parking areas, access ramps and all other surfaces.
- This asphalt is applied by compaction, no heat is required.
- bomix® asphalt remains workable down to a temperature of 5 °C (41 °F).

2- Installation

2.1 SURFACE PREPARATION

- Thoroughly clean area to be resurfaced with a heavy broom or a brush. Remove all loose matter, earth, grass, etc..
- If required, use a chisel to clean the damaged area.
- It is suggested to clean at least 5 cm (2 in) in thickness.

2.2 APPLICATION

- Fill the area with bomix® asphalt to approximately 12 mm (1/2 in) above the level of surrounding pavement.
- Level with a lawn roller, a hand-stamper or the flat face of a shovel. NOTE: Resistance will depend on the degree of compaction. This step is very important.
- bomix® asphalt does not require any curing time, the surface may be used as soon as the work is completed however, the asphalt does not harden instantly. Care must be taken with sharp objects such as shoe heels.

- Hardening may take up to 12 days to happen and is slower in hot weather.

2.3 YIELD

- A 30 kg (66 lb) bag will cover approximately 0,014 m³ (0,5 ft³).

2.4 CLEANING

- Mineral spirit is an excellent solvent to clean tools.

3. Packaging

- This product is available in 30 kg (66 lb) plastic bag.

4. Storage

- Store in a cool, dry place. Keep away from heat sources.
- Shelf life is two years in unopened bags.

5. First aid

This product contains naphtha and may cause eye and skin irritation. Wear rubber gloves and safety glasses. If swallowed, call a Poison Control centre or doctor immediately. Give approximately 250 ml of water to the victim if she is conscious. Do not induce vomiting. In case of contact with eyes, rinse well with water for 15 minutes. In case of skin contact, rinse well with water. Keep out of reach of children. Consult the safety data sheet for more information.

6. Technical services

Contact Daubois for more information about application methods or conditions or to obtain the latest version of our technical documents.

Phone: 1-800-561-2664
(514) 328-1253

Fax: (514) 328-7694

Daubois inc
6155, boul. des Grandes Prairies
Saint-Léonard, Qc H1P 1A5
Canada
<http://www.daubois.com>

7. Warranty

Daubois guarantees that this product will perform as specified in this technical data sheet and suits the application for which it was intended. Nonetheless, Daubois does not offer any explicit or implicit warranty. Under this warranty, Daubois' responsibility is limited to either replace or refund the cost of the product proved defective.